

SP500 Series Dot Matrix Printers

The SP500 sets a new standard for design, features and performance in dot matrix printers.



Features:

- High performance, high reliability, long life receipt printers
- Over 4 Lines Per Second Printing Speed
- Internal Universal Power Supply - 100 to 240 VAC 50/60Hz
- Tear Bar & Autocutter Models
- Windows, OPOS and JavaPOS Drivers
- Exceptional Value & Performance

The SP500 series offers two models, each with a choice of two communications interfaces, the SP512 tear bar model, and the SP542 auto cutter model. For communications, the SP500 series are available with either parallel (IEEE1284) or serial (RS232C) interfaces. Aesthetic integration is fostered by the availability of two popular case colors: charcoal gray and putty.

At over 4 lines/sec (at 42 columns per line) printing speed, the SP500 is among the fastest dot matrix printers currently on the market. Its print head contains the latest in print head technology, providing improved response times and increased reliability over previously available technology. This 9-pin print head, coupled with a stepping motor paper feed, allows the SP500 series to print high-quality graphics and extended characters. The logic seeking mechanism of the SP500 increases the efficiency of the print mechanism, while also aiding in improving print speed.

SP500 Series Product Specifications

Print Speed	Over 4 lps
Auto-Cutter	SP542 (Full & Partial Cut)
No. of Columns	42
Paper Specs	Standard Roll Paper
Width	76 mm default, 58 mm adjustable
Thickness	0.07- 0.10 mm Copies: Original + 2 copies (Max. 0.20 mm)
Roll Diameter	85mm (max.)
Paper Roll Core	12±1 mm ID, 18±1mm OD
Loading	Semi-Automatic
Paper Sensors	Paper out

Reliability	
Printer	MCBF 22 Million lines, Printhead - 70 Million characters
Cutter	0.5 Million cuts
Operating Conditions	
Temperature	0°C to 40°C
Humidity	10% to 90% RH
Interface	Serial (RS232C) or Parallel (IEEE1284)
Emulation	Star Mode, ESC/POS™
Cash Drawer	2 Drivers, 1 Compulsion Switch
Auto-Cutter	SP542 (Full & Partial Cut)
Drivers	Windows9x/NT/2000, OPOS, JavaPOS™
Case Color	Putty or Charcoal
Supply Voltage	100 to 240V AC, 50/60Hz
Ribbon	RC200B, RC200P
Dimensions	140 (W) x 225 (D) x 163 (H)